

West Boundary of T. 23 S., R. 5 W., W.M.

CHAINS

- A Y. oak, 14 ins. diam., bears N.17°E., 55 lks.
- A Y. oak, 18 ins., diam., bears S.49°E., 78 lks.
- A Y. oak, 15 ins. diam., bears S.43°W., 77 lks.

Land, all hilly.

North half, oak openings.

Soil, 2d rate.

South half, principally timbered with fir.

Undergrowth, hazel, ninebark, fern, briars, etc.

Soil, 3d rate.

May 5, 1853

South Boundary of T. 23 S., R. 5 W., W.M.
Same Deputies and Contract

The partially completed dependent resurvey of T. 23 S., R. 6 W. was made by Mr. Gould just before he was transferred from field to office, he has therefore, furnished me with the following statement:

"The preliminary retracements of part of T. 23 S., R. 6 W., W. M., Oregon were made in 1943 by Otis O. Gould. Before he left in the fall corners were established around sections 1, 2, 11, 12, 13 and 36. This survey is not approved and is unofficial. $\frac{1}{2}$ sec. and section corners were left at the temporary points on most of the east half of the township, none that are not set were at old corners. Since Mr. Gould left the field the old $\frac{1}{2}$ sec. cor. of secs. 13 and 14 has been found about 2 or 3 chains S. and a little to the west of where the $\frac{1}{2}$ sec. cor. was proportioned in and established."

(Quoted from a letter from Geo. F. Rigby to Ben B. Irving, County Surveyor, dated December 29, 1954.)

	N.89°44'W, on South boundary of Sec. 36.	
17.50	A trail, course N and S.	+100
24.00	Leave prairie, course N.20°E., and S.	-80
26.00	A stream, 15 lks. wide, course S.	-15
40.00	Set $\frac{1}{2}$ sec. post, from which	+30
	A Y. oak, 16 ins. diam., bears N.33°E., 53 lks.	
	A W. oak, 15 ins. diam., bears S.57 $\frac{1}{2}$ °E., 163 lks.	
		Va.18°20'E
51.20	A stream, 3 lks. wide, course SE.	+70
80.00	Set post, cor. to secs. 35, 36, 1 and 2 from which	+80
	A Y. oak, 18 ins. diam., bears S.11 $\frac{1}{2}$ °E., 126 lks.	