

North Boundary of T. 24 S., R. 6 W., W.M.  
 Surveyed by Elder A. Gile, Deputy Surveyor, under Contract No. 31  
 Dated April 7th, 1853

CHAINS		
	West, on North Boundary, Sec. 1.	
		Va. 19°15'E.
9.00	A Stream, 2 lks. wide, course South	-80
31.00	Top of Ridge, course N. and S.	+100
40.00	Set $\frac{1}{2}$ sec. post from which	-150
	A Laurel, 6 ins. diam., bears S. 51° W. 26 lks.	
	A Laurel, 10 ins. diam., bears N. 39° E. 10 lks.	
45.76	A Fir, 30 ins. diam.	-80
52.50	Begin to ascend mountain NE & SW.	-15
71.50	Top of Spur, course SE.	+300

The partially completed dependent resurvey of T. 23 S., R. 6 W. was made by Mr. Gould just before he was transferred from field to office, he has therefore, furnished me with the following statement:

"The preliminary retracements of part of T. 23 S., R. 6 W., W. M., Oregon were made in 1943 by Otis O. Gould. Before he left in the fall corners were established around sections 1, 2, 11, 12, 13 and 36. This survey is not approved and is unofficial.  $\frac{1}{2}$  sec. and section corners were left at the temporary points on most of the east half of the township, none that are not set were at old corners. Since Mr. Gould left the field the old  $\frac{1}{2}$  sec. cor. of secs. 13 and 14, has been found about 2 or 3 chains S. and a little to the west of where the  $\frac{1}{2}$  sec. cor. was proportioned in and established."

(Quoted from a letter from Geo. F. Rigby to Ben B. Irving, County Surveyor, dated December 29, 1954.)

	West, on true line on North Boundary of Sec. 2.	
		Va. 19°00'E.
4.45	A Stream, 3 lks. wide, course S.80°E.	-25
22.25	A Fir, 12 ins. diam.	+800
28.00	Top of mountain, course N.& SW.	+80
40.00	Set $\frac{1}{2}$ sec. post, from which	+75
	A Fir, 14 ins. diam., bears N.37°W., 33 lks.	
	A Fir, 15 ins. diam., bears S.23°E., 18 lks.	
		Va. 19°05'E.
49.52	A Fir, 50 ins. diam.	-150
58.75	A stream, 3 lks. wide, course NW.	-100
63.50	Top of Spur, course NW.	-75
65.78	To unpassable cliff, course SW & NE.	-60