

Subdivision of T. 23 S., R. 6 W., W.M.

CHAINS 64.00	Top of Bald Spur, course E.& W.	+150
65.00	A very fair view. The top of a snow covered mountain in the Willamette is visible. Commence ascending burnt East hillside.	
76.50	Divide between the waters of Calapooya and Yellow Creek, commence descent.	+50
80.00	Set post, in head of timberflat, for cor. secs. 25, 26, 35 and 36, from which  A Fir, 15 ins. diam., bears S.83½* W., 41 lks.	-10

The partially completed dependent resurvey of T. 23 S., R. 6 W. was made by Mr. Gould just before he was transferred from field to office, he has therefore, furnished me with the following statement:

"The preliminary retracements of part of T. 23 S., R. 6 W., W. M., Oregon were made in 1943 by Otis O. Gould. Before he left in the fall corners were established around sections 1, 2, 11, 12, 13 and 36. This survey is not approved and is unofficial. ¼ sec. and section corners were left at the temporary points on most of the east half of the township, none that are not set were at old corners. Since Mr. Gould left the field the old ¼ sec. cor. of secs. 13 and 14 has been found about 2 or 3 chains S. and a little to the west of where the ¼ sec. cor. was proportioned in and established."

(Quoted from letter from Geo. F. Rigby to Ben B. Irving, County Surveyor, dated December 29, 1954.)

80.24	Intersect 40 lks. S. of post to cor. secs. 25 and 36, T. 23 S., R. 6 W., and secs. 30 and 31, R. 5 W., from which  A White Oak 10 ins. diam., bears N.34*E., 185 lks. A White Oak 7 ins. diam., bears N.82*W/, 523 lks. A White Oak 12 ins. diam., bears S.26*E., 490 lks.  Agreeably to your field notes, but A White Oak 13 ins. diam., bears S.6*W., 436 lks. dist., and not S.60*W.  <div style="text-align: right;">March 13th, 1879</div> On true line bet. secs. 25 and 36. <div style="text-align: right;">Va.19*25'E. Latitude.89*43'W.</div>	+10
10.00	Top of Ascent, commence descending	
17.00	Enter Prairie	