

11

Subdivision of T 23 S., R 6 W.

CHAINS 41.00	A Ridge, course NW	+500
63.10	A Fir, 36 ins. diam.	
70.00	A Ridge, course N.29*W.	+800
72.25	A Hemlock, 20 ins. diam.	
80.00	Set Dogwood post 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to Secs. 11, 12, 13 and 14 Marked T 23 S S 12 on NE., R 6 W S 13 on SE., S 14 on SW., and S 11 on NW face with 4 notches on S and 1 notch on E. edge, from which A Laurel, 12 ins. diam., bears N.12*E., 38 lks. dist. Marked T 23 S R 6 W S 12 B T A Laurel, 10 ins. diam., bears S.10*E., 20 lks. dist. Marked T 23 S R 6 W S 13 B T A Fir, 18 ins. diam., bears S.70*W., 8 lks. dist.	

The partially completed dependent resurvey of T. 23 S., R. 6 W. was made by Mr. Gould just before he was transferred from field to office, he has therefore, furnished me with the following statement:

"The preliminary retracements of part of T. 23 S., R. 6 W., W. M., Oregon were made in 1943 by Otis O. Gould. Before he left in the fall corners were established around sections 1, 2, 11, 12, 13 and 36. This survey is not approved and is unofficial. $\frac{1}{4}$ sec. and section corners were left at the temporary points on most of the east half of the township, none that are not set were at old corners. Since Mr. Gould left the field the old $\frac{1}{4}$ sec. cor. of secs. 13 and 14 has been found about 2 or 3 chains S. and a little to the west of where the $\frac{1}{4}$ sec. cor. was proportioned in and established."

(Quoted from a letter from Geo. F. Rigby to Ben B. Irving, County Surveyor, dated December 29, 1954.)

	East on random line bet. Secs. 12 & 13.	↑ to Hedge
	Va. 19 $\frac{1}{2}$ *E.	
	Through Timber	
10.32	A Hemlock, 20 ins. diam.	
16.80	A Brook, 2 lks. wide, course NW.	
23.50	A Ridge, course NW & SE	-500
37.20	A Fir, 36 ins. diam.	
40.00	Set temp. $\frac{1}{4}$ sec. cor.	
49.20	A Cedar, 18 ins. diam.	