

County Surveyor's Record, Douglas County, Oregon

2457

West Boundary of T. 23 S., R. 7 W., W. M. as surveyed by
 Thomas H. Hutchinson, Deputy Surveyor, under contract No. 60,
 dated July 19, 1855.

| CHAINS | | |
|--------|--|------|
| | <p>Begin at the post, the established corner to township 23 South in Ranges 7 and 8 West, on the 5th standard parallel South. The witness trees all standing,</p> <p style="text-align: right;">Viz:</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.42*W., 6 lks. dist.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S.65*E., 15 lks. dist.</p> <p>South on (a true line) Range line, between Ranges 7 and 8 West, and on West Boundary of sec. 6. Variations by Burt's Improved Solar Compass. 19*30'E.</p> | |
| 38.00 | Summit of ridge, course E. & W. Leave oak brush and enter prairie, bearing E. & W. | +60 |
| 40.00 | <p>Set a post for quarter sec. cor. from which,</p> <p style="padding-left: 40px;">A black oak, 18 ins. diam., bears N.7*E., 266 lks. dist.</p> <p style="padding-left: 40px;">A black oak, 18 ins. diam., bears N.3*W., 255 lks. dist.</p> | -300 |
| 80.00 | <p>Set a post for cor. to secs. 6, 7, 1 & 12, from which,</p> <p style="padding-left: 40px;">A white oak, 20 ins. diam., bears N.70*E., 80 lks. dist.</p> <p style="padding-left: 40px;">A white oak, 4 ins. diam., bears S.35*W., 88 lks. dist.</p> <p>No other trees convenient to mark, raised mound with pits as per instruction.</p> <p>First 38.00 chs., oak brush. Timber scattering oak & fir. Remainder smooth prairie. Descent 150 ft. in 42.00 chs. Soil first rate.</p> | -150 |
| | <p>South on a true line along the West Boundary of sec. 7.</p> <p style="text-align: right;">Va. 19*30'E.</p> | |
| 20.00 | Enter oak brush, course E. & W. | |
| 39.00 | Leave oak brush and enter prairie, course E. & W. | -40 |
| 40.00 | <p>Set a quarter sec. post, from which,</p> <p style="padding-left: 40px;">an ash, 8 ins. diam., bears N.12*W., 317 lks. dist.</p> | |