

County Surveyor's Record, Douglas County, Oregon

-32-

Subdivision and Meander Lines of T. 23 S., R. 7 W., W. M.

CHAINS		
38.00	Summit of river bluffs, course N E & S W.	+150
40.00	Set $\frac{1}{4}$ sec. post from which, A fir, 25 ins. diam., bears N.4*E., 50 lks. dist. A fir, 35 ins. diam., bears S.4*W., 100 lks. dist.	-150
45.00	To Umpqua river set post cor. to fractional secs. 4 and 5 on right bank of river, from which A fir, 30 ins. diam., bears East, 20 lks. dist. A fir, 48 ins. diam., bears S.80*W., 55 lks. dist. To ascertain the dist. across the river, I cause a flag to be set at fractional cor. on left bank between secs. 4 and 5 which is South. I now take a base by measure- ing West 1.48 chs. From this point the flag on left bank bears S.5*E., which gives for dist. across river 16.94 chs. The entire length of this line between secs. 4 and 5 is 79.84 chs. Namely: South of river 17.90 chs., across the river 16.94 chs., North of river 45.00 chs. or total of 79.84 chs. Land very broken. Soil 3rd rate. Timber scattering oak and fir.	-150
	North between secs. 31 and 32. Va. 19*30'E.	
40.00	Set $\frac{1}{4}$ sec. post, from which, A chittem. wood, 4 ins. diam., bears N.78*W., 32 lks. dist. A hazel, 3 ins. diam., bears S.50*E., 23 lks. dist.	
68.37	Left bank of Umpqua river where set post for cor. to fractional secs. 31 and 32, from which, A fir, 36 ins. diam., bears West, 93 lks. dist. A myrtle, 10 ins. diam., bears East, 4 lks. dist. To ascertain the width of the river I leave a flag at the above cor. and cross the river and set my compass on true line between secs. 31 and 32. I measure East for a base 3.50 chs. From this point the flag bears S.20*W.,	-150