

County Surveyor's Record, Douglas County, Oregon
-66-

Subdivisions of T. 23 S., R. 7 W., W. M.

CHAINS	<p>A fir, 8 ins. diam., bears N.15*E., 30 lks. dist. A maple, 12 ins. diam., bears S.15*W., 41 lks. dist.</p>
79.50	Creek 3 lks. wide, course SW.
80.14	To sec. cor.
	Land mountainous, 3rd rate. Heavily timbered, chiefly fir & cedar.
	North on random line between sec. 1 & 2. Va. 19*E.
35.00	Top of rocky spur, course E.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
89.25	Intersect North boundary at cor. established for cor. to secs. 1 & 2 on N boundary of T.
	South on true line.
3.00	Top of ridge, course E & W. Leave timber.
20.00	Enter timber, course E & W.
49.25	Set fir post for the $\frac{1}{4}$ sec. cor., from which, A fir, 60 ins. diam., bears S.45*E., 10 lks. dist. A fir, 16 ins. diam., bears S.25*W., 42 lks. dist.
55.00	Begin steep descent.
89.25	To sec. cor.
	Land South part rocky, 3rd rate. North part good 2nd rate. Timber chiefly fir.
	Feb. 16th, 1881.
	Begin at the cor. to secs. 34 & 35., South boundary of T. Thence North on old line between said secs. Va. 19*30'E.
40.22	$\frac{1}{4}$ sec. cor. witness trees standing. Set new post, from same, viz: AA fir, 18 ins. diam., bears S.9*E., 192 lks. A fir, 10 ins. diam., bears S.5*W., 381 lks.