

County Surveyor's Record, Douglas County, Oregon

EXTERIOR BOUNDARIES T. 23 S., R. 8 W.

CHAINS

I begin at the cor. to secs. 7, 12, 13 and 18, T. 23 S., R's. 8 & 9 W. which is a post 4 ins. square marked

T 23 S S 7 on N.E.
R 8 W S 18 on S.E.
R 9 W S 13 on S.W. and
S 12 on N.W. faces

with 2 notches on N. and 4 notches on S. edges from which:

A fir, 36 ins. diam., bears N. 15° E. 45 lks. dist., mkd. T 23 S R 8 W S 7 BT.

A chinquapin, 16 ins., diam., bears S. 52° E., 36 lks. dist., marked T23S R8W S18 BT.

A maple, 14 ins. diam., bears S. 60° W., 15 lks. dist. marked T23S R9W S13 BT.

A fir, 16 ins. diam., bears N. 70° W. 12 lks. dist. marked T23S R9W S12 BT.

Thence, I run South btwn. Twps. 23 S., R's. 8 and 9 West.

I set temporary half-mile corners at each 40 and 80 chs. and at 4 miles, 14 chains and 61 links reach a point 37.09 chains west of the closing corner at N. W. corner Twp. 24 S., R. 8 W., at which point

I set a post 4½ ft. long 4 ins. square, 24 ins. in the ground, for closing corner at S. W. corner to T. 23 S. R. 8 W., marked:

CC T 23 S on N.
R 8 W S 31 on E and
R 9 W S 36 on W

with 6 notches on N. & E. sides, from which:

A fir, 24 ins. diam., bears N. 28° E. 60 lks. dist., marked T23S R8W S31 BT.

A fir, 24 ins. diam., bears N. 25° W. 28 lks. dist., marked T23S R9W S36 BT.

A fir, 16 ins. diam., bears S. 58° W. 14 lks. dist., marked T23S R8 & 9 W. CC BT.

The closing corner at N. W. corner, T. 24 S., R. 8 W. is a Stone 10 x 6 x 5 ins. above ground marked CC with 6 notches on S. and E. edges from which:

A fir, 18 ins. diam., bears N. 14° E. 53 lks. dist., marked T marked T. 24 S R8 W. CC BT.

A fir, 18 ins. diam., bears S. 22° E. 71 lks. dist., marked T24S R8W S6 BT.

A fir, 12 ins. diam., bears S. 40° W., 10 lks. dist., marked T23S R9W S36 BT.

+ + + + + + + + + + + +

Note - Survey by W. R. Whipple, dated 1894.

ADDED TO NOTES FEB. 1967

LL