

County Surveyor's Record, Douglas County, Oregon

West Boundary of T. 23 S., R. 8 W., W. M.

.CHAINS.

40.00

A point about 400 ft. below top of mountain. Set a post 3 ins. sq., 3 ft. long, 2 ft. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on W face, from which,

A fir, 20 ins. diam., bears S.10°E., 27 lks. dist., marked $\frac{1}{4}$ S B T.

A hemlock, 8 ins. diam., bears N.45°W., 27 lks. dist., marked $\frac{1}{4}$ S B T.

44.90

Stream 2 lks. wide, course NW about 200 ft. below $\frac{1}{4}$ sec. corner. Ascend gradually over W slope.

50.70

Stream 1 lk. wide, course W.

53.40

The $\frac{1}{4}$ sec. cor. on E. boundary of sec. 1 T. 23 S., R. 9 W.

82.21

A point 8.75 chs. W of the SW cor. to Tp. 22 S., R. 8 W., which is a point 4 ins. sq. marked T 22 S on N; R 8 W S 31 on E and R 9 W S 36 on W with 6 notches on N, E & W sides, from which,

A fir, 40 ins. diam., bears N.65°W., 118 lks. dist., marked T 22 S R 9 W S 36 B T.

A fir, 60 ins. diam., bears N.70°E., 137 lks. dist., marked T 22 S R 8 W S 31 B T.

Set a post 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground for NW cor. to Tp. 23 S., R. 8 W., marked R 8 W S 6 on E; T 23 S on S and R 9 W on W, with 6 notches on S & E sides, from which,

A fir, 20 ins. diam., bears S.30°E., 45 lks. dist., marked T 23 S R 8 W S 6 B T.

A fir, 40 ins. diam., bears N.40°W., 41 lks. dist., marked T 23 S R 9 W S 1 B T.

NW cor. T. 23 S., R. 8 W., (CORRECTED AS FOLLOWS:)

I obliterate marks relating to R. 9 W. on post and B T and mark on NW BT, T 23 S R 8 W S 6 B T.

A dogwood, 5 ins. diam., bears N.12°E., 60 lks. dist., which I mark T 23 S R 8 W S 6 B T.

June 21st, 1896.