

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 23 S., R. 8 W., W. M.

CHAINS

44.10 Stream, 1 lk. wide, course SW about 100 ft. below $\frac{1}{4}$ sec. cor.

50.60 A stream, 2 lks. wide, course S and ascend.

56.25 Top of a ridge, course S about 200 ft. high and descend.

69.00 Stream, 1 lk. wide, course S.20*E., about 250 ft. below top of ridge and ascend.

80.00 Top of a spur on S slope about 300 ft. high and descend.

81.44 The cor. to secs. 13, 14, 23 and 24.

Land, 74.94 chs. mountainous.

Soil, 3rd and 4th rate. East 6.50 chs. level bottom; soil 1st rate, sandy loam.

Heavily timbered with fir, cedar, maple and chinquapin. 76.34 chs.

Dense undergrowth of hazel, sallal, fern and briars. 73.34 chs.

N.0*1'W., on a random line, bet. secs. 13 and 14.

Va.20*33'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

81.17 The cor. to secs. 11, 12, 13 and 14 bears East 19 lks. dist.

The post and the SE and NW bearing trees being gone, I reestablish the cor. by setting a stone, 14x12x6 ins., 10 ins. in the ground for cor. to secs. 11, 12, 13 and 14 with 4 notches on S and 1 notch on E edges from which

A fir, 16 ins. diam., bears N.20*E., 35 lks. dist., instead of 38 lks. dist., as per reference notes, marked T 23 S R 8 W S 12 B T.

A fir, 30 ins. diam., bears S.1*W., 25 lks. dist., as per reference notes, marked T 23 S R 8 W S 14 B T.

A fir, 6 ins. diam., bears S.76*E., 97 lks. dist., which I mark T 23 S R 8 W S 13 B T.