

Subdivisions of T. 23 S., R. 8 W., W. M.

51.75	CHAINS Top of a spur, course NE., 150 ft. high.
80.00	A point about 250 ft. below top of last spur. This point falling on solid bed rock. I made a cross (x) at the exact corner point with 2 notches S and 3 notches E, from corner point, from which, <p style="margin-left: 40px;">A hemlock, 24 ins. diam., bears N.22*E., 87 lks. dist., marked T 23 S R 8 W S 22 B T.</p> <p style="margin-left: 40px;">A fir, 50 ins. diam., bears S.81½*E., 205 lks. dist., marked T 23 S R 8 W S 27 B T.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S.11*W., 100 lks. dist., marked T 23 S R 8 W S 28 B T.</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N.20*W., 124 lks. dist., marked T 23 S R 8 W S 21 B T.</p> <p>Land mountainous 80 chs. Soil 3rd & 4th rate. Timber fir, cedar, & hemlock. Dense undergrowth of rhododendron, sallow and vine maple.</p>
	East on a random line between secs. 22 & 27. Va. 20*35'E.
40.00	Set temporary ¼ sec. cor.
80.76	Intersect N & S line 12 lks. N of cor. to secs. 22, 23, 26 & 27. Thence, I run N.89*55'W., on a true line between secs. 22 & 27. Va. 20*35'E.
	Ascend through timber.
6.50	Top of a spur, course N.20*E.
22.00	Top of a ridge, course N., about 400 ft. above cor & descend.
32.20	Stream 1 lk. wide, course N.10*W.
34.25	Stream 1 lk. wide, course N.20*W.
40.38	Set a sandstone 14 x 12 x 10 ins., 10 ins. in the ground for ¼ sec. cor., marked ¼ on N face, from which, <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N.70*W., 10 lks. dist., marked ¼ S B T.</p> <p style="margin-left: 40px;">A hemlock, 12 ins. diam., bears S.53*E., 24 lks. dist., marked ¼ S B T.</p>