

## County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 23 S., R. 8 W., W. M.

CHAINS	
	edges from which A fir, 6 ins. diam., bears N.40°E., 58 lks. dist., marked T 23 S R 8 W S 16 B T. A fir, 24 ins. diam., bears S.82°E., 105 lks. dist., marked T 23 S R 8 W S 21 B T. A fir, 40 ins. diam., bears S.24°W., 33 lks. dist., marked T 23 S R 8 W S 20 B T. A fir, 30 ins diam., bears N.18°W., 79 lks. dist., marked T 23 S R 8 W S 17 B T. Land mountainous 80.00 chs. Soil 2nd & 3rd rate. Timber Fir, cedar, maple and hemlock. Undergrowth of hazel, sallow, vine maple and rhododendron.
	S.89°49'E., on a random line, between secs. 16 & 21. Va. 20°35'E.
40.00	Set temporary $\frac{1}{4}$ sec. cor.
80.26	Intersect N & S line 50 lks. N. of cor. to sec. 15, 16, 21 & 22. Thence N.89°28'W. on a true line between Secs. 16 & 21. Va. 20°40'E.
	Over S. slope ascending.
3.00	Top of a little spur, course S. descend.
7.20	Stream 3 lks. wide, course S., about 100 ft. below top of spur. Ascend.
23.00	Top of a little spur, course S., about 300 ft. above stream. Descend about 50 ft. then ascend.
40.13	Set a sandstone 16 x 12 x 10 ins., 12 ins. in ground, marked $\frac{1}{4}$ on N. face from which, A fir, 16 ins. diam., bears S.38°W., 19 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 30 ins. diam., bears N.73°E., 141 lks. dist., marked $\frac{1}{4}$ S B T.
45.75	Top of a spur, course S., descend.