

## County Surveyor's Record, Douglas County, Oregon

-15-

## Subdivision of T. 23 S., R. 8 W., W. M.

CHAINS	
57.00	Top of a spur, course W., about 400 ft. above stream,
73.80	Top of a ridge, course E & W.
80.00	Set stone 16 x 12 x 8 ins., 10 ins. in the ground for corner to secs. 4, 5, 8 & 9, marked with 5 notches on S. and 4 notches on E. edges, from which, A fir, 30 ins., diam., bears N.15°E., 57 lks. dist., marked T 23 S R 8 W S 4 B T. A fir, 20 ins. diam., bears S.10°E., 70 lks. dist., marked T 23 S R 8 W S 4 B T. A fir, 30 ins. diam., bears S.21°W., 30 lks. dist., marked T 23 S R 8 W S 8 B T. A fir, 24 ins. diam., bears N.67°W., 38 lks. dist., marked T 23 S R 8 W S 5 B T. Land mountainous 80 chs. Soil 3rd & 4th rate. Timber fir, cedar and maple. Undergrowth of vine maple, hazel and sallal. 80 chs.
	S.89°10'E., on a random line between Sec. 4 & 9. Va. 20°30'E.
40.00	Set temporary $\frac{1}{4}$ sec. Cor.
79.93	Intersect N & S line 43 lks. S. of cor. to sec. 3, 4, 9, & 10. Thence N.89°28'W., on a true line between secs. 4 & 9. Va. 20°50'E.
	Descend.
14.40	Stream 3 lks. wide, course N.80°W.
15.10	Stream 10 lks. wide, course N. Ascend.
39.97	Set a stone 12 x 8 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on North face, from which, A fir, 14 ins. diam., bears S.73°W., 34 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 48 ins. diam., bears N.53°E., 31 lks. dist., marked $\frac{1}{4}$ S B T.