

County Surveyor's Record, Douglas County, Oregon  
32

Subdivision of T. 23 S., R. 8 W., W. M.

CHAINS

Heavily timbered with fir, hemlock, cedar and maple.  
Dense undergrowth of thimbleberry, sallal, vine maple,  
huckleberry and briars. 83.37 chs.

May 24th, 1894.

In order to properly connect my work, I found it necessary  
to resurvey the lines between secs. 24 & 25; 1 & 2; and  
2 & 11, which I do as follows:

I begin at the cor. to secs. 19, 24, 25 & 30 on the E.  
boundary of the township which is a post 4 ins. sq.,  
marked T 23 S S 19 on N E., R 7 W S 30 on S E., R 8 W S  
25 on S W., and S 24 on N W. faces with 4 notches on N  
and 2 notches on S. edges, from which,

A fir, 40 ins. diam., bears N.62\*E., 438 lks.  
dist., marked T 23 S R 7 W S 19 B T.

A fir stump, 40 ins. diam., bears S.8\*E., 650 lks.  
dist., marks obliterated.

A W. oak, 20 ins. diam., bears S.16\*W., 650 lks.  
dist., marked T 23 S R 8 W S 25 B T.

A fir, 70 ins. diam., bears N.29\*W., 95 lks.  
dist., marked T 23 S R 8 W S 24 B T.

Thence S.89\*51'W., retracing line between secs 24 & 25.

Va. 20\*30'E.

Descend in clearing.

6.50 Leave same course, N & S.89\*E., and enter brush and  
timber.

40.88  $\frac{1}{4}$  sec. cor. which is a post 3 ins. sq., marked  $\frac{1}{4}$  S on  
North face, from which,

A W. oak, 7 ins. diam., bears N.80\*W., 5 lks.  
dist., marked  $\frac{1}{4}$  S B T.

A fir, 24 ins. diam., bears S.5\*E., 70 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

80.66 The corner to secs. 23, 24, 25 & 26.