

## County Surveyor's Record, Douglas County, Oregon

-1-

Subdivisions of T. 23 S., R. 9 W. W.M.  
as surveyed by W.H. Byars, Deputy Surveyor under  
Contract No. 279, dated March 5, 1878.

## CHAINS

Begin at the cor. to Secs. 12, 13, 7, and 18, on  
Tp. line between ranges 8 and 9 W.

West in true line between Secs. 12 and 13.

Va. 19\*E.

- 3.50 Camp Creek, 100 lks wide, course NW.
- 40.00 Set Fir post 4 ins. diam. 40 ins. lg. for  $\frac{1}{4}$  Sec. cor  
from which,  
A Fir, 60 ins. diam., bears N.50\*E. 47 lks. dist.  
A Fir, 6 ins. diam., bears S.45\*W. 8 lks. dist.
- 43.50 Creek, 2 lks. wide, course NE.
- 71.00 Top of spur, course N.
- 80.00 Marked a Hemlock 5 Ins. diam. for the corner to Secs.  
11, 12, 13 and 14, from which  
A Fir, 18 ins. diam., bears N.60\*E. 100 lks, dist.  
A Maple, 18 ins. diam., bears S.71\*E. 60 lks, dist.  
A Fir, 36 ins. diam., bears S. 60\*W 27 lks. dist.  
A Fir, 60 ins. diam., bears N.12\*W. 30 lks. dist.  
Land broken, rocky, 3rd rate.
- 
- N. on true line between Secs. 11 and 12.  
Va. 19\*E.
- 21.00 Creek, 1 lk. wide, course N.10\*E.
- 40.00 Set Maple post for  $\frac{1}{4}$  Sec. corner, from which,  
A Fir, 18 ins. diam., bears East 19 lks. dist.  
A Fir, 40 ins. diam., bears N.75\*W. 47 lks. dist.
- 67.00 Camp Creek, course W.  
March 22rd, 1878
- 80.00 Set post, a Fir, 4 ins. diam., 4 ft long 20 ins. in  
ground for the corner to Secs. 1, 2, 11 and 12, from  
which,  
A Fir, 14 ins. diam., bears N.22\*E. 68 lks. dist.  
A Hemlock, 8 ins. diam., bears S.45\*E. 20 lks. dist.  
A Fir, 12 ins. diam., bears S.50\*W 58 lks. dist.  
A Fir, 8 ins. diam., bears N.70\*W. 33 lks. dist.  
Land broken, 3rd rate. Narrow bottom along creek  
1st rate.  
Timber good