

County Surveyor's Record, Douglas County, Oregon

- 4 -

Subdivisions of T. 23 S., R. 9W. W.M.
as surveyed by W.H. Byars, Deputy Surveyor under
Contract No. 279, dated March 5, 1878.

CHAINS

S. on true line between Secs. 4 and 5.

Va. 19*E.

13.00 Camp Creek, 75 lks. wide, course S.75*W.

27

March 26th, 1878.

27.00 Creek, 3 lks. wide, course E.

40.00 Set Fir, post 5 ft. long 6 ins. diam. 24 ins. in ground
for $\frac{1}{4}$ Sec. corner, from which

A Fir, 48 ins. diam., bears S.20*E. 90 lks. dist.

A Fir, 48 ins. diam., bears S.15*W. 85 lks. dist.

61.00 Creek, 2 lks. wide, course E.

80.00 Set Maple post 4 ins. diam. 4 ft. long, 18 ins. in
ground for corner to Secs. 4, 5, 8 and 9.

A Fir, 40 ins. diam., bears N.35*E. 82 lks. dist.

A Fir, 48 ins. diam., bears S.25*E. 26 lks. dist.

A Fir, 30 ins. diam., bears S.37*W. 58 lks. dist.

A Fir, 30 ins. diam., bears N.45*W. 75 lks. dist.

This line runs near small creek.

Land, 2nd rate.

Timber, fir, good.

W. on true line between Secs. 5 and 8.

Va. 19*E.

10.00 Creek, 2 lks. wide, course S.88*E.

40.00 Set a Dogwood post for $\frac{1}{4}$ Sec. corner, from which

A Fir, 30 ins. diam., bears South 21 lks. dist.

A Fir, 36 ins. diam., bears N.60*W. 48 lks., dist.

63.50 Top of ridge, course NE. and SW.

80.00 Set a Fir post 5 ins. diam. 4 ft. long, 20 ins. in
ground for the corner to Secs. 5, 6, 7, and 8, from
which,

A Hemlock, 14 ins. diam., bears N.87*E. 58 lks. dist.

A Hemlock, 24 ins. diam., bears S.65*E. 80 lks. dist.

A Fir, 48 ins. diam., bears S.82*W. 138 lks. dist.

A Hemlock, 48 ins. diam., bears N.72*W. 84 lks. dist.

Land, high mountainous, 3rd rate.

Timber, Fir and Hemlock, 3rd class.