

County Surveyor's Record, Douglas County, Oregon

-6-

North Boundary of T. 24 S., R. 9 W., W.M.,
as surveyed by W.H. Byars, Deputy Surveyor, under
Contract No. 292, dated August 7, 1878

CHAINS	
	From the NE. corner of Township S.89*35'W., on N. bdy. of Sec. 1 Va. 18'E.
10.00	Bed of dry creek, 10 lks. wide, course NW.
29.50	Creek, 2 lks. wide, course N.
32.00	Creek, 2 lks. wide, course N.
40.00	Set a Cedar post, 40 ins. long, 5 ins. diam., 18 ins. in ground for the $\frac{1}{4}$ sec. corner on North boundary of sec. 1, from which A Cedar, 12 ins. diam., bears N.31 lks. dist. A Fir, 30 ins. diam., bears S.20*W., 17 lks. dist.
80.00	Set Fir post, 38 ins. long, 5 ins. diam., 18 ins. in ground for the corner to Sec. 1 and 2, North bdy. post in edge of creek, 2 lks. wide, from which A Fir, 16 ins. diam., bears N.55*E., 75 lks. dist. A Fir, 8 ins. diam., bears S.88*E., 114 lks. dist. A Fir, 40 ins. diam., bears S.89*W., 75 lks. dist. A Fir, 6 ins. diam., bears N.70*W., 50 lks. dist.
	Land, broken; 3rd rate. Timber, chiefly Fir. Underbrush, same, Vine-maple, Alder and Hazel.
	S.89*35'W. on North bdy. of Sec. 2, Va. 18'E.
38.00	A creek, 1 lk. wide, course North.
40.00	Set a Dogwood post, 3 ft. long, 5 ins. diam., 18 ins. in the ground for the $\frac{1}{4}$ sec. corner on North bdy. of Sec. 2, from which, A Fir, 35 ins. diam., bears S.5*E., 25 lks. dist. A Fir, 30 ins. diam., bears N.40*W., 17 lks. dist.
70.00	Enter creek bottom, course NE. and SW.
73.00	A creek, 25 lks. wide, course S.75* <u>W.</u>
79.00	Leave creek bottom, course S.75* <u>W.</u>
80.00	Set Fir post, 40 ins. long, 5 ins. diam., 18 ins. in the ground for the corner to sec. 2 and 3 on North bdy. from which, A Fir, 60 ins. diam., bears N.1*E., 8 lks. dist.