

East Boundary of T. 23 S., R. 10 W., W.M.

CHAINS

Corner between sections 13 and 18, from which,

A Maple, 10 ins. diam., bears S.16\*E., 100 lks.  
dist.

A Fir, 60 ins. diam., bears N.30\*W., 37 lks. dist.

72.50 Creek, 2 lks. wide, course NW.

80.00 Marked a Hemlock, 24 ins. diam., for sec. corner to  
secs. 7, 12, 13 and 18, from which,

A Fir, 48 ins. diam., bears N.20\*E., dist. 42 lks.

A Fir, 48 ins. diam., bears S.30\*E. 36 lks. dist.

A Fir, 30 ins. diam., bears S.30\*W., 53 lks. dist.

A Fir, 24 ins. diam., bears N.45\*W., 2 lks. dist.

Land, South part first rate; North part 3rd rate.

Timber same as former line.

Underbrush same.

N. on E. Bdy. of sec. 12

Va. 19\*E.

28.50 Creek, 10 lks. wide, course SW.

September 24th, 1878

40.00 Set Chinquapin post, 36 x 5, 18 ins. in ground for  
the  $\frac{1}{4}$  sec. corner between secs. 7 and 12.

A Fir, 16 ins. diam., bears N.3\*E., 100 lks.  
dist.

A Fir, 24 ins. diam., bears S.60\*E., 38 lks.  
dist.

67.00 Creek, 2 lks. wide, course W.

80.00 Set a Laurel post, 36 x 4, 18 ins. in ground for the  
corner to secs 1, 6, 7, and 12, from which,

A Laurel, 5 ins. diam., bears N.2\*E., 7 lks.  
dist.