

County Surveyor's Record, Douglas County, Oregon

17

Subdivisions of T. 23 S., R. 9 W., W.M.

CHAINS	W. on random line between secs. 18 and 19 Va. 19*E.
40.00	Set Temp. $\frac{1}{4}$ sec. corner.
80.06	Intersect at corner East on true line between secs. 18 and 19.
3.00	Soup Creek, 40 lks. wide, course NW.
4.00	Soup Creek, 40 lks. wide, course SW.
5.50	Soup Creek, 40 lks. wide, course N.80*W.
21.50	Leave valley. Gradual ascent.
46.03	Set Fir post, 5 ft. long 5 ins. diam., 20 ins. in ground for the $\frac{1}{4}$ sec. corner between secs. 18 and 19, from which, A Fir, 48 ins. diam., bears N.20*E., 42 lks. dist. A Fir, 40 ins. diam., bears S.70*E., 25 lks. dist.
52.25	A creek, 2 lks. wide, course S.
65.00	Enter valley, course SW.
79.70	Creek, 30 lks. wide, course S.
80.06	To sec. corner Land, 1st and 2nd rates. Timber, same as previous lines on hills, Maple, Ash, Willow and Crab in bottoms.
May 12, 1879	
	N. on line between secs. 17 and 18 Va. 19*E.
0.50	Creek, 30 lks. wide, course SW.
13.00	Leave valley, course NE. and SW.
20.00	Creek, 1 lks. course SE.
40.00	Set Maple post, 5 ft. long, 5 ins. diam., 20 ins. in ground for the $\frac{1}{4}$ sec. corner between secs. 17 and 18, from which, A Hemlock, 30 ins. diam., bears N.50*E., 37 lks. dist. A Hemlock, 36 ins. diam., bears S.72*W., 40 lks. dist.
41.00	A creek, 2 lks. wide, course E.
49.25	A creek, 2 lks. wide, course SE.
69.25	A creek, 2 lks. wide, course SE.
80.00	Set a Chinquapin post, 5 ft. long, 5 ins. diam., 20 ins. (in the