

Subdivisions of T. 23 S., R. 9W., W.M.
Same Deputy and Contract

CHAINS

ground for the corner to Secs. 7, 8, 17 and 18,
from which,

A Fir, 60 ins. diam., bears N.10*E. 62 lks. dist.

A Fir, 20 ins. diam., bears S.60*E. 42 lks. dist.

A Fir, 50 ins. diam., bears S.45*W. 27 lks. dist.

A Fir, 40 ins. diam., bears N.60*W. 15 lks. dist.

Land, hilly, 3rd rate.

Timber and underbrush same as former lines.

W. on random line between Secs. 7 and 18.

Va. 19*E.

40.00 Set temp. $\frac{1}{4}$ Sec. corner

80.20 Intersect line 35 lks. S. of corner

S.89*45'E. on true line between Secs. 7 and 18.

40.20 Set a Fir post 5 ft long 5 ins. diam., 20 ins. in
ground for the $\frac{1}{4}$ Sec. corner between Secs. 7 and 18,
from which,

A Fir, 40 ins. diam., bears N.20*E. 20 lks. dist.

A Fir, 30 ins. diam., bears S.25*W. 32 lks. dist.

67.50 A creek, 2 lks. wide, course N.

80.20 To Section corner.

Line runs near top of high ridge.

Land, 3rd rate.

Timber and underbrush continues unchanged.

May 13th, 1879.

Beginning at the corner to Secs. 19, 20, 29 and 30

I run,

East on a true line between Secs. 20 and 29.

Va. 19*E.

3.50 A creek, 2 lks. wide, course N.

13.50 A creek, 3 lks. wide, course NW.

40.00 Set Hemlock post 5 ft. long, 5 ins. in diam. 20 ins.
in ground for the $\frac{1}{4}$ Sec. cor between Secs. 20 and
29, from which

A Maple, 24 ins. in diam., bears N.45*E. 24 lks.