

County Surveyor's Record, Douglas County, Oregon

- 19 -

Subdivisions of T. 23 S., R. 9W., W.M.
Same Deputy and Contract

CHAINS	
	A Hemlock, 20 ins. diam., bears S.40*W. 42 lks. dist.
42.00	A creek, 5 lks. wide, course N.
62.00	Top of high spur, course N.
75.25	A creek, 5 lks. wide, course N.
80.00	Set a Cedar post 5 ft. long, 5 ins. in diam. 20 ins. in ground for the corner to Secs. 20, 21, 28 and 29, from which, A Hemlock, 12 ins. in diam., bears N.45*E. 5 lks. dist. A Fir, 8 ins. in diam., bears S.35*E. 23 lks. dist. A Fir, 8 ins. in diam., bears S.18*W. 29 lks. dist. A Fir, 16 ins. in diam., bears N.25*W. 11 lks. dist. Land, mountainous, 3rd rate. Timber, unchanged.
	N. on true line between Secs. 20 and 21 Va. 19*E.
17.00	Enter valley, course NW.
21.50	Creek 15 lks. wide, course N.W.
24.00	Leave valley, course NW.
40.00	Set Yew post 50 ins. long 5 ins in diam. 20 ins. in ground for the $\frac{1}{4}$ Sec. corner between Secs. 20 and 21, from which, A Cherry, 6 ins. in diam., bears East 20 lks. dist. A Cherry, 60 ins. in diam., bears S5*W. 43 lks. dist.
46.00	Enter valley, course W.
51.00	Creek, 40 lks. wide, course W.
52.00	Leave valley
73.50	Creek, 2 lks., course SE.
80.00	Set Dogwood post 5 ft. long 5 ins. in diam. 20 ins. in ground for the Sec. corner between Secs. 16, 17, 20 and 21, from which, A Fir, 16 ins. in diam., bears N.10*E. 33 lks. dist. A Fir, 20 ins. in diam., bears S.88*E. 26 lks. dist. A Fir, 48 ins. in diam., bears S.60*W. 16 lks. dist. A Fir, 20 ins. in diam., bears N.70*W. 9 lks. dist. Land, mountainous, 3rd rate. Timber unchanged.