

County Surveyor's Record, Douglas County, Oregon

-20-

Subdivisions of T. 23 S., R. 9 W., W.M.
Same Deputy and Contract

CHAINS W. on random line between Secs. 17 and 20.
Va. 19*E.

40.00 Set temp. $\frac{1}{4}$ Sec. corner

80.30 Intersect line 28 lks. North of corner
North 89*48'E. on true line between Secs. 17 and 20.

1.50 Begin ascent

33.00 Top of ridge, course SW.

36.00 Trail to valley.

40.15 Set Maple post 5 ft. long 5 ins. in diam. 20 ins. in
ground for $\frac{1}{4}$ sec. corner between Secs. 17 and 20,
from which,
A Fir, 8 ins. diam., bears S.80*E. 10 lks. dist.
A Fir, 48 ins. diam., bears N.35*W. 25 lks. dist.

80.30 To section corner
Land 3rd rate.
Timber and underbrush unchanged.

May 15th, 1879

The surveys made in this township includes all the
lands capable of being occupied, the remainder being
generally high rugged mountains.

The valleys along the streams are 1st quality of
land, generally covered with Maple, Ash and Salmon-
berry bushes. Mountains covered with Fir, Cedar,
Hemlock, Maple and a few other varieties.

Underbrush same and Salmonberry, Sallall, Sarvice
and some other brush.

South Boundary of T. 23 S., R. 9 W., W.M.
as surveyed by Oscar F. Thiel, Deputy Surveyor
under Contract No. 689, dated June 9, 1898.

S. 39*35'W. bet Secs. 36 and 1.

Descending the N. side of a ridge, covered heavily by
fir, cedar and hemlock timber.

11.20 A stream, 1 lk. wide, course N., 100 ft below initial
corner., begin ascent

August 17: At 12 $\frac{1}{2}$ 5 $\frac{1}{2}$ P.M. 1.m.t. I set off 13*14'N.,