

County Surveyor's Record, Douglas County, Oregon

- 24 -

South Boundary of T. 23 S., R. 9 W., W.M.
as surveyed by Oscar F. Thiel.

CHAINS 46.08	Cor. of Secs. 3 and 4, which is a sandstone 48 x 24 ins. above ground, marked and witnessed as described by the surveyor general, I destroyed all marks, referring to this township.
47.20	Lake Creek, 50 lks, wide, course N.75*W.
53.00	Lake Creek, 50 lks. wide, course S.65*W.
54.00	Begin an ascent of a steep SE. slope, covered heavily with fir timber.
	August 19: at 8 ^h 30 ^m A.M., l.m.t., I set off 12*39'N. on the decl. arc; 43*31' on the lat. arc, and determine a true meridian with the solar at this point.
63.20	Top of spur, bears N. and S., 150 ft. above creek. Begin descent of W. slope.
78.10	A stream, 5 lks. wide, course S. 200 ft. below top of spur.
80.00	A point at foot of mountain Set a Vine-maple post, 3 ft. long, 4 ins. sq. 24 ins. in ground for cor. of Secs. 33 and 34 marked T 23 S S 34 on NE., and R 9W S 33 on NW. face with 3 notches on E. and W. edges, from which, An Alder, 20 ins. diam., bears N.39*E., 28 lks. dist. marked T 23 S R 9 W S 34 B T. A Fir, 48 ins. diam., bears N.11*W., 46 lks. dist., marked T 23 S R 9 W S 33 B T. Land, mountainous. Soil, loamy and gravelly, 1st and 3rd rate. Timber, Fir, Cedar, Hemlock, Maple, Alder. Undergrowth, dense and of Fir, Hemlock and Alder. Mountainous, heavily timbered land and covered by dense undergrowth, 80.00 chs.
	S. 89*35'W. bet Secs. 33 and 4.
	A steep ascent of E. slope of mountain covered heavily with fir timber.
5.93	The old $\frac{1}{4}$ sec. corner post being gone, I replace the cor.