

County Surveyor's Record, Douglas County, Oregon

- 25 -

South Boundary of T. 23 S., R. 9 W., W.M.
as surveyed by Oscar F. Thiel

CHAINS

- by setting a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, marked and witnessed as described by the surveyor general.
- 25.50 Top of spur, bears N. and S., 250 ft. above sec. cor., begin a steep descent of mountain, covered by a dense undergrowth of Huckleberries and Arrow wood and heavily timbered with Fir.
- 32.00 A stream, 2 lks. wide, course S. 150 ft. below top of spur, begin to ascend.
- August 19: At this point, I set off $12^{\circ}36'N$. on the decl. arc; and at 0^h4^m P.M., l.m.t. observe the sun on the meridian, the resulting lat. is $43^{\circ}31'$.
- 40.00 A Maple, 6 ins. diam., for $\frac{1}{4}$ sec. cor. which I marked $\frac{1}{4}$ S 33 on N. side, from which
- A Maple, 4 ins. diam., bears $S84^{\circ}W$, 19 lks. dist. marked $\frac{1}{4}$ S 33 B T.
- A Fir, 5 ins. diam., bears $N.24^{\circ}E$., 37 lks. dist., marked $\frac{1}{4}$ S 33 B T.
- 45.85 Cor. of Sec. 4 and 5, there is a fir post, 5 ins. diam., 24 ins. high, very much decayed, marked and witnessed as described by the surveyor general. I destroy all marks, referring to this township. It stands on top of a spur, bearing $S.70^{\circ}W$. and $N.70^{\circ}E$., 180 ft. above stream, begin descent.
- 57.20 A stream, 1 lk. wide, course SW. 100 ft. below $\frac{1}{4}$ sec. cor. Begin to ascend mountain, enter an old burn of timber, bears N. and S.
- 75.50 Top of ridge, bears NE. and SW., 220 Ft. above stream. Leave burn, begin to descend a NW. slope of mountain.
- 80.00 Set a sandstone 18 x 16 x 5 ins., 12 ins. in the ground for cor. of secs. 32 and 33, marked with 4 notches on E. and 2 notches on W. edges, from which,
- A Fir, 40 ins. diam., bears $N.1^{\circ}E$., 310 lks. dist. marked T 23 S R 9 W S 33 B T.
- A Fir, 24 ins. diam., bears $N.45^{\circ}W$., 26 lks. dist., marked T 23 S 9 W S 32 B T.