

## County Surveyor's Record, Douglas County, Oregon

- 31 -

Subdivisions of T. 23 S., R. 9 W., W.M.  
same Deputy and Contract.

CHAINS	
	W. bet secs. 36 and 35.
	Along S. slope of mountain, covered heavily with timber
6.75	Top of dividing ridge, bears NE. and SW., 50 ft. above sec. cor., begin a steep descent of NW. slope of mountain.
37.50	A stream, 5 lks. wide, course S., 300 ft. below ridge, begin to ascend.
	Aug. 26, 1898
40.00	A point 50 ft. above stream; I set a sandstone 22 x 12 x 6 ins., 17 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, from which, A Chinquapin, 6 ins. diam., bears S3*E., 18 lks. dist. marked $\frac{1}{4}$ S 35 B T. A Fir, 4 ins. diam., bears N.64*E., 19 lks. dist., marked $\frac{1}{4}$ S 26 B T.
41.00	Enter a dense undergrowth of small firs, greasewood and huckleberries, bears N. and S.
54.00	A stream, 1 lk. wide, course S., enter large fir timber bears N. and S. August 27: At this point at 9 <sup>h</sup> 5 <sup>m</sup> A.M., l.m.t., I set off 43*32' on the lat. arc; 9*55'N., on the decl arc; and determine a true meridian with the solar.
63.50	A stream, 3 lks. wide, course S.75*E., along a timber bench; slightly ascending.
80.00	A point 75 ft. above stream, I set an alder post, 3 ft. long, 4 ins. sq, 24 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, marked T 23 S S 26 on NE.; R 9 W S 35 on SE. S 34 on SW; and S 27 on NW. faces, with 1 notch on S and 2 notches on E. edges, from which An Alder, 10 ins. diam., bears N.53*E., 7 lks. dist. marked T 23 S R 9 W S 26 B T. A Hemlock, 6 ins. diam., bears S 51 $\frac{1}{2}$ *E., 47 lks. dist. marked T 23 S R 9 W S 35 B T.