

County Surveyor's Record, Douglas County, Oregon

-35-

Subdivisions of T. 23 S., R. 9 W., W.M.
same Deputy and Contract.

CHAINS

79.60 and 2.18 chs.

August 30, 1898.

- August 31: At 9^h5^m A.M., l.m.t., I set off 43*32' on the lat. arc; 8*28.5'N. on the lat,arc *****
S.89*35'W. on a random line bet. secs. 29 and 32
- 43.05 Intersect N. and S. line 240 lks. N. of cor. of secs. 29, 30, 31 and 32, which is
A Fir, 24 ins. diam., marked and witnessed as described by the surveyor general,
I set, at the point of intersection, a sandstone, 12 in. by 9 by 5 ins. in the ground for closing cor. of secs. 29 and 32, marked C C on E; with 1 groove on S. and 5 grooves on E. faces; from which,
A Maple, 4 ins. diam., bears N.37*E., 22 lks. dist. marked T 23 S. R 9 W S 29 B T.
A Dogwood, 3 ins. diam., bears S23*E., 48 lks. dist. marked T 23 S R 9 W S 32 B T.
I destroyed all marks on old corner and bearing trees, referring to these secs.
N.89*35'E. on true line bet. secs. 29 and 32.
Continue to ascend heavily timbered mountain spur.
- 3.80 Top of mountain ridge, bears SW. and NE., begin to descend a steep E. slope.
- 40.00 Set a Fir post, 3 ft long, 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 29 on N. face and 32 on S. face, from which,
A Fir, 30 ins. diam., bears S.79*W., 33 lks. dist., marked $\frac{1}{4}$ S.32 B T.
A Fir, 20 ins. diam., bears N.76*W., 37 lks. dist., marked $\frac{1}{4}$ S 29 B T.
Along a benchland, covered with a dense undergrowth of huckleberry, vinemaple, and salal berries.
- 42.40 A stream, 2 lks. wide, course SW.