

Subdivisions of T. 23 S., R. 9 W., W.M.  
same Deputy and Contract.

CHAINS	
24.00	The descent becomes more abrupt.
31.60	A stream, 5 lks. wide, course SW., 250 Ft. below top of ridge; begins a steep ascent.
33.40	A stream, 3 lks. wide, course SE.; continue to ascend.
40.00	A point, 120 ft. above stream; I set a Dogwood post, 3 ft. long, 3 ins. sq, 24 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 7 on W. face, from which A Fir, 40 ins. diam., bears S.50*W., 51 lks. dist. marked $\frac{1}{4}$ S 7 B T. A Fir, 24 ins. diam., bears N.23E., 35 lks. dist., marked $\frac{1}{4}$ S 7 B T. Continue to ascend.
64.00	Top of spur, bears E. and W., 150 Ft. above $\frac{1}{4}$ sec. cor., begin a descent.
68.60	A stream, 1 lk. wide, course W.
83.50	Top of spur, bears E. and W., 300 ft. above last stream; begin an easy descent of N. slope.
97.25	A top of a ridge, bears SE. and NW.; go along through large firs and hemlock.
115.00	Begin a steep ascent of S. slope
119.30	Intersect E. and W. line 32.75 chs. E. of cor to secs. 5,6,7 and 8, which is a fir post 5 ins. sq, 24 ins. high, badly decayed, marked and witnessed as described by the surveyor general. I destroyed all marks referring to secs. 7 and 8. At the point of intersection, I set an alder post, 3 ft.long. 4 ins. sq., 24 ins. in the ground, for closing cor. of secs. 7 and 8, marked C C T 23 S R 9 W on S.; S 8 on E. and S 7 on W. faces with 5 grooves on E. and S. faces from which, A Fir, 40 ins. in diam., bears S.32*E. 57 lks., dist, marked T 23 S R 9 W S 8 B T. A Fir, 30 ins. in diam., bears S.63*W., 60 lks., dist, marked T 23 S R 9 W S 7 B T. This cor stands on S. side of summit of ridge. Land, mountainous.