

## County Surveyor's Record, Douglas County, Oregon

- 41 -

Subdivisions of T. 23 S., R. 9 W., W.M.  
same Deputy and Contract.

## CHAINS

- Begin gradual descent of W. slope.
- 40.00 Set a Maple post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S 9 on N. face and 16 on S. face, from which,  
 A Fir, 50 ins. diam., bears N.17\*E., 59 lks. dist., marked  $\frac{1}{4}$  S 9 B T.  
 A Fir, 60 ins. diam., bears S.66\*W., 30 lks. dist., marked  $\frac{1}{4}$  S 16 B T.
- Continue descending.
- 45.20 A stream, 4 lks. wide, course N., 100 ft. below  $\frac{1}{4}$  sec. cor.
- 51.35 A stream, 3 lks. wide, course NE., begin to ascend.
- 59.50 Top of spur, bears N. and S., 150 ft. above stream, Begin to descend.
- 65.75 A stream, 2 lks. wide, course N., thence along on a timber bench, through old burns of timber.
- 78.00 A dim trail, bears NW. and SE., begin ascent.
- 80.00 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 8,9, 16 and 17, marked T 23 S S 9 on NE.; R 9 W S 16 on SE.  
 S 17 on SW., and S 8 on NW. face, with 4 notches on S. and E. edges, from which  
 A Fir, 40 ins. diam., bears N.89\*E., 72 lks. dist. marked T 23 R 9 W S 9 B T.  
 A Fir, 26 ins. diam., bears S.54\*E., 51 lks. dist. marked T 23 S R 9 W S 16 B T.  
 A Fir, 6 ins. diam., bears S.46\*W, 103 lks. dist. marked T 23 S. R 9 W S 17 B T.  
 A Fir, 30 ins. diam., bears N.9\*W., 80 lks. dist. marked T 23 S R 9 W S 8 B T.
- Cor. stands 60 ft. below top of ridge.
- Land, mountainous.
- Soil, clayey loam; 2nd rate.