

Subdivisions of T. 23 S., R. 9 W., W.M.
same Deputy and Contract.

CHAINS

- N.0*1'W., on line bet secs. 23 and 24.
- Ascend a spur of mountain, covered heavily with Fir
timber.
- 2.50 Top of spur, bears E. and W., begin a steep descent into
a canyon.
- 7.45 A stream, 3 lks. wide, course E., 85 ft. below top of
spur, begin ascent.
- 15.40 A Fir, 48 ins. diam., on line, I mark with 2 notches on
N. and S. sides; stands on top of spur, bearing E. and
W.; begin a steep descent.
- 32.10 A stream, 1 lk. wide, course E., 250 ft. below top of
spur; begin to ascend.
- 37.15 Top of spur, bears E. and W., begin to descend.
- 40.00 Set a sandstone, 24 x 10 x 5 ins., 15 ins. in the
ground for $\frac{1}{4}$ sec. cor, marked $\frac{1}{4}$ on W. face, from which,
A Fir, 60 ins. diam., bears S.60*E., 50 lks. dist.,
marked $\frac{1}{4}$ S 24 B T.
A Fir, 45 ins. diam., bears N.25*W., 57 lks. dist.,
marked $\frac{1}{4}$ S 23 B T.
This cor. stands 60 ft. below top of spur.
- 40.50 Foot of descent, begin to ascend.
- 44.00 Top of spur, bears E. and W., begin descent.
- 49.50 The descent becomes steeper, a N. slope.
- 55.30 A stream, 6 lks. wide, course E., 150 ft. below spur.
- 58.40 D.W. Owen's Trail to Lake Creek, bears E. and W.,
Begin a steeper ascent of S. slope.
- 66.61 A Fir, 26 ins. diam., on line, which I mark with 2
notches on S. and N. sides.
- 75.00 Top of mountain ridge, bears SE. and NW., 200 ft. above
stream.
- 80.00 Set a Hemlock post, 3 ft. long, 4 ins. sq., 24 ins.
in the ground, for cor. of secs. 13, 14, 23 and 24,
marked T 23 S 13 on NE.: R 9 W S 24 on SE.
S 23 on SW and S 14 on NW. faces, with notch on E
and 3 notches on S. edges, from which
A Maple, 18 ins. diam., bears N.12*E., 47 lks. dist.