

-50-

Subdivisions of T. 23 S., R. 9 W., W.M1

## CHAINS

- 115.42 Intersect E. and W. line 62 lks. E. of Cor. of Secs. 11, 12, 13, and 14, described previously.
- September 14, 1898
- Cor. of Secs. 11, 12, 13 and 14
- S.0°19'E. on a true line bet. secs. 13 and 14.
- Ascend very sharply, to the dividing ridge, bears E. and W., covered heavily with timber.
- 4.40 Top of divide, bears E. and W., begin to descend.
- 23.70 A stream, 1 lk. wide, course E. begin ascent, 225 ft. below divide; dense undergrowth of small hemlocks.
- 26.10 Top of spur, bears E. and W.
- 36.75 A stream, 2 lks. wide, course E., begin steep ascent of N. slope.
- 46.70 The ascent moderates; along a timber bench, covered heavily with large firs.
- 52.70 Top of a spur, bears E. and W., descend a SE. slope.
- 75.42 Set a Hemlock post, 5 ft. long, 4 ins. sq, 24 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S 14 on W. and 13 on E. face, from which,
- A Maple, 14 ins. diam., bears N.87 $\frac{1}{2}$ \*E., 40 lks. dist. marked  $\frac{1}{4}$  S 13 B T.
- A Fir, 30 ins. diam., bears N.77\*W., 41 lks. dist., marked  $\frac{1}{4}$  S 14 B T.
- Continue to descend; cor is 150 ft. below spur.
- 79.85 A stream 4 lks. wide, course E.
- 87.80 A stream, 2 lks. wide, course E., begin a steep ascent of N. slope.
- 90.90 The ascent changes from N. slope to NE. slope.
- 96.00 Top of steep ascent, ascent moderates.
- 100.50 Top of ridge, bears E. and W., begin to descend.
- 110.50 A dry gulch, course SE., 150 ft. below top of ridge.
- 115.42 The cor. of secs. 13, 14, 23 and 24.
- Land, mountainous
- Soil, gravelly and 3rd rate.