

County Surveyor's Record, Douglas County, Oregon

- 57 -

Subdivisions of T. 23 S., R. 9 W., W.M.

CHAINS

At noon, it commenced raining preventing further work this day.

September 22, 1898.

S.0*23' E. on a true line bet. secs. 15 and 14

Descend mountain slope, covered heavily with fir and hemlock timber, dense undergrowth of small hemlock, vine-maple and huckleberries.

- 3.00 A stream, 2 lks. wide, course E., continue to ascend E. slope of mountain.
- 22.50 A stream, 1 lk. wide, course E., continue ascend E. slope.
- 37.50 A stream, 3 lks. wide, course E. continue ascent.
- 51.30 A stream, 2 lks. wide, course NE.
- 56.10 Top of ridge, bears E. and W., 100 ft. above stream, begin to descend.
- 64.85 A stream, 2 lks. wide, course NE., begin ascent.
- 71.35 Top of ridge, bears E. and W., 100 ft. above stream, begin to descend.
- 76.13 A point 50 ft. below top of ridge, set a hemlock post 3 ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 15 on W. face and 14 on E. face, from which,
 A Hemlock, 7 ins. diam., bears S.20*E., 13 lks. dist. marked $\frac{1}{4}$ S 14 B T.
 A Maple, 20 ins. diam., bears S.39*W., 35 lks. dist. marked $\frac{1}{4}$ S 15 B T.
- Continue to descend.
- 78.90 A stream, 2 lks. wide, course E. 75 ft. below cor.
- 83.40 A stream, 1 lk. wide, course E.
- 86.45 A stream, 1 lk. wide, course NE., begin ascent.
- 96.00 Top of spur, bears NE. and SW., 175 ft. above stream; along E. slope.
- 105.60 A spring branch, course E.
- 114.00 Begin to ascend.