

County Surveyor's Record, Douglas County, Oregon

-73-

Subdivisions of T. 23 S., R. 9 W., W.M.

CHAINS

A Fir, 40 ins. diam., bears N.50*E., 48 lks. dist.
marked T 23 S R 9 W S 16 B T.

A Fir, 36 ins. diam., bears N.64*W., 69lks. dist.
marked T 23 S R 9 W S 17 B T.

June 1st, at this cor., I set off took my bearings and
thence I run,

N.89*48'E. on true line, bet. secs. 16 and 20.

Ascending gradually S. side of mountain, covered heavily
with fir and hemlock timber.

22.50 Top of ascent, 80 ft. above sec. cor.; begin descent
of E. slope.

32.60 NE. cor. of sec. 20. Thence I run
N.0*3'W., bet secs. 16 and 21

4.10 Set hemlock post, 3 ft long, 4 ins. sq., 24 ins. in the
ground for NW. cor. of sec. 21, marked
T 23 N S 16 on NE.; R 9 W S 21 on SE., S 16 on SW.,
and S 16 on NW. faces, with 4 notches on E. and 3
notches on S. edges, from which

A Hemlock, 20 ins. diam., bears S.61*E., 35 lks. dist.
marked T 23 S R 9 W S 21 B T.

Thence I run, E. on a true line bet. secs. 16 and 21.

On bench land, covered heavily with timber.

40.00 Set a hemlock post, 3 ft. long, 3 ins. sq., 24 ins. in
the ground, marked $\frac{1}{2}$ S 16 on N. face and S.21 on S. face
from which

A Fir, 55 ins. diam., bears N.72*E., 25 lks. dist.,
marked T 23 S R 9 W S 16 B T.

A Fir, 12 ins. diam., bears S.4 $\frac{1}{2}$ *E., 37 lks. dist.,
marked $\frac{1}{2}$ S. 21 B.T.

Follow timber bench land.

54.00 Begin to descend

59.00 The descent becomes steeper.

62.00 A stream, 2 lks. wide, course SE., 140 ft. below $\frac{1}{2}$ sec.
cor., continue descending.