

## County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 23 S., R. 10 W., W. M. as surveyed by  
W. H. Byars, Deputy Surveyor, under contract No. 292  
dated August 7, 1878.

CHAINS	<p>East on random line on South Boundary of T. 23 S., R. 10 W. Secs. 31, 32, 33, 34, 35 and 36.</p> <p style="text-align: right;">Va. 19*East.</p> <p>Set temporary half mile and mile post at every 40 and 80 chains and at 6 miles and 50 lks. intersect line 1.50 chains South of established corner to Tp's 23 &amp; 24 S. R's 9 and 10 West.</p> <p>The correction will be 50 lks. West and 25 links South for each mile or South 89*49' West on true line.</p> <p style="text-align: right;">May 21st and 22nd, 1879.</p>
	<p>South 89*49'W on South Bdy. of Sec. 36.</p> <p style="text-align: right;">Va. 18*E.</p> <p>5.00 Lake Creek, 150 lks. wide, course SW.</p> <p>8.25 Steep bluff, impassable, rocky. S.45*W., 2.00 chs; West 3.50 chs; N.45*W., 2.00 chs.</p> <p>14.58 To line above bluff.</p> <p>16.00 Top of hill, course SW.</p> <p>20.00 Steep descent.</p> <p>25.50 Lake Creek, 150 wide, course N.</p> <p>28.00 Steep ascent, rocky.</p> <p>35.00 Top of spur, course N.</p> <p>40.00 Set a maple post 5 ft. long, 5 ins. diam., 20 ins. in ground for the <math>\frac{1}{4}</math> sec. cor. between secs. 1 &amp; 36, from which</p> <p style="padding-left: 40px;">A fir, 60 ins. diam., bears N.15*E., 23 lks. dist.</p> <p style="padding-left: 40px;">A maple, 5 ins. diam., bears S.30*E., 26 lks. dist.</p> <p>Post sets near foot of hill.</p> <p>57.00 Begin steep descent.</p> <p>78.60 A creek, 100 lks. wide, course N.</p> <p>80.00 Set a fir post 5 ft. long, 5 ins. diam., 20 ins. in the ground for the corner to secs. 1, 2, 35 and 36, from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N.70*E., 95 lks. dist.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.80*E., 106 lks. dist.</p>