

## County Surveyor's Record, Douglas County, Oregon

## Subdivisional Lines of T. 23 S., R. 10 W.

CHAINS

- 27.00 Leave same.
- 30.00 Trail, course N & S.
- 31.50 Lagoon, 100 lks. wide, course N & S.
- 36.00 Lake Creek, 100 lks., course N.
- 38.00 Same, course SW, 100 lks.
- 40.46 Set maple post, 4 ft. long, 5 ins. diam., 18 ins. in the ground for the  $\frac{1}{2}$  sec. cor. between secs. 24 & 25, from which
- A myrtle, 16 ins. diam., bears North, 43 lks. dist.
- An alder, 5 ins. diam., bears South, 10 lks. dist.
- 47.50 Lake Creek, 100 lks. wide, course N.
- 60.00 Cabin south of line about 3 chains.
- 66.50 Creek, 5 lks. wide, course NE.
- 68.00 Leave bottom, course NE.
- 80.92 To sec. cor.
- Land, 1st class.
- Timber chiefly myrtle, maple, fir etc.
- Underbrush same.
- 
- North between secs. 23 & 24.
- Va. 20\*E.
- 17.25 Creek, 3 lks. wide, course E.
- 40.00 Set a fir post, 4 ft. long, 18 ins. in ground, 5 ins. diam., for the  $\frac{1}{2}$  sec. cor. between secs. 23 & 24, from which
- A hemlock, 30 ins. diam., bears S.30\*E., 20 lks. dist.
- A cedar, 36 ins. diam., bears S.25\*W., 23 lks. dist.
- 40.50 Creek, 3 lks. wide, course E.
- 57.25 Creek, 2 lks. wide, course SE.
- 74.00 Top of spur; course E.
- 80.00 Set a yew post, 4 ft. long, 5 ins. diam., 18 ins. in the ground for the cor. to secs. 13, 14, 23 & 24, from which
- A hemlock, 10 ins. diam., bears N.85\*E., 24 lks. dist.
- A fir, 30 ins. diam., bears S.25\*E., 67 lks. dist.