

## Subdivisions of T. 23 S., R. 10 W.

## CHAINS

S.0\*1'E., on a true line bet. secs. 33 and 34  
 Descend steep mountain through dense undergrowth  
 8.30 Branch, 3 lks. wide, 100 ft. below sec. cor.; course W.  
 Enter heavy timber  
 20.50 Summit of ridge, 250 ft. above branch, bears NW. and SE.  
 40.00 Set a hemlock post, 3 ft. long, 4 ins. sq. 24 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S 33 on W., and 34 on  
 E face, from which  
     A hemlock, 20 ins. diam., bears S.69\*E., 39 lks.  
     dist. Marked  $\frac{1}{4}$  S 34 B T  
     A fir, 30 ins. diam., bears N.74\*W., 51 lks. dist.  
     Marked  $\frac{1}{4}$  S 33 B T  
 50.30 A branch, 2 lks. wide, 300 ft. below summit of ridge;  
     course W.  
 58.36 J. N. Price's house, bears East, 38.90 chs. dist.  
 60.00 Point of spur, sloping S.  
 69.00 Summit of mountain, 300 ft. above branch and descend  
 80.50 Branch, 1 lk. wide, 100 ft. below summit; course S.10\*W.  
 81.28 Intersect Tp. line, 6.62 chs. N.89\*49'E., of C. C. for  
     secs. 3 and 4, set by Gesner and Warrick, under Contract  
     No. 659, which is a hemlock post, 5 ins. sq. 1 ft. above  
     ground, firmly set, marked and witnessed as described  
     by the Surveyor General  
 At point of intersection  
 Set a hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the  
 ground, for C. C. of secs. 33 and 34, marked  
 C C T 23 S R 10 W on N.,  
 S 34 on E., and  
 S 33 on W. face, with 3 grooves on E. and W. faces  
 from which  
     A fir, 30 ins. diam., bears N.6\*E., 29 lks. dist.  
     Marked T 23 S R 10 W S 34 B T  
     A fir, 16 ins. diam., bears N.73\*W., 66 lks. dist.  
     Marked T 23 S R 10 W S 33 B T