

Subdivisions of T. 23 S., R. 10 W.

CHAINS

70.20

Top of spur on bare rock, slopes E., 100 ft. above branch.

80.00

Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 9, 10, 15 and 16, marked

T 23 S S 10 on NE.,

R 10 W S 15 on SE.,

S 16 on SW., and

S 9 on NW. face,,with 4 notches on S., and 3 notches on E. edge; from which

A fir, 6 ins. diam., bears N.20*E., 34 lks. dist.

Marked T 23 S R 10 W S 10 B T

A fir, 8 ins. diam., bears S.52*E., 32 lks. dist.

Marked T 23 S R 10 W S 15 B T

A fir, 10 ins. diam., bears S.39*W., 30 lks. dist.

Marked T 23 S R 10 W S 16 B T

A fir, 6 ins. diam., bears N.28*W., 23 lks. dist.

Marked T 23 S R 10 W S 9 B T

Land, mountainous

Soil, 3rd rate

Timber, fir and some hemlock

Undergrowth, small fir, hemlock, huckleberry and salmon-berry

Land, mountainous, heavily timbered or covered with dense undergrowth, 80.00 chs.

July 26, 1906.

At the cor. of secs. 9, 10, 15 and 16

Thence I run

S.89*51'E., on a random line bet. secs. 10 and 15.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

74.81

The cor. of secs. 10, 11, 14 and 15, which is a post, marked and witnessed as described by the Surveyor General, bears S.0*12'E., 1.52 chs. dist.

This close being in excess of the prescribed limits, I