

## Subdivisions of T. 23 S., R. 10 W.

CHAINS	
40.50	A fir snag, 48 ins. diam., on line I mark with 2 notches on N. and S. sides.
54.00	Begin to descend rapidly, 100 ft. below $\frac{1}{4}$ sec. cor.
67.50	A creek, 15 lks. wide, 700 ft. below $\frac{1}{4}$ sec. cor.; course S.70*E.  Leave burn and ascend steep mountain through dense undergrowth and live timber
78.20	Foot of rocky ledge, 40 ft. high, extending E. and W.
79.00	Top of rocky ledge; continue ascent  At a point 200 ft. above creek
80.00	Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, marked T 23 S S 2 on NE., R 10 W S 11 on SE., S 10 on SW and S 3 on NW. face, with 5 notches on S., and 2 notches on E. edge; from which  An alder, 6 ins. diam., bears N.55*E., 4 lks. dist. Marked T 23 S R 10 W S 2 B T  An alder, 7 ins. diam., bears S.75*E., 15 lks. dist. Marked T 23 S R 10 W S 11 B T  A fir, 6 ins. diam., bears S.43*W., 22 lks. dist. Marked T 23 S R 10 W S 10 B T  A fir, 4 ins. diam., bears N.25*W., 28 lks. dist. Marked T 23 S R 10 W S 3 B T  Land, mountainous  Soil, rocky, 3rd rate  Timber, fir and alder  Undergrowth, small fir, alder and vine maple  Land, mountainous, heavily timbered or covered with dense undergrowth, 80.00 chs.