

Subdivisions of T. 23 S., R. 10 W.

CHAINS

At the cor. of secs. 2, 3, 10 and 11.

Thence I run,

N.0°1'W., on a true line bet. secs. 2 and 3.

Ascend over mountainous land through heavy timber and dense undergrowth.

13.00 Summit of spur, 200 ft. above sec. cor., sloping S.30°E.

Descend mountainside, sloping E.

25.40 A stream, 3 lks. wide, 200 ft. below summit of spur; course E.

40.00 At top of steep descent.

Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S 3 on W., and 2 on E. face, from which

A fir, 30 ins. diam., bears N.36°E., 24 lks. dist. marked $\frac{1}{4}$ S 2 B T.

A fir, 30 ins. diam., bears S.48°W., 25 lks. dist. marked $\frac{1}{4}$ S 3 B T.

Descend.

42.80 Branch, 2 lks. wide, course E.

43.05 Branch, 2 lks. wide, 150 ft. below $\frac{1}{4}$ sec. cor., course E.

50.00 Descend steep hillside, sloping NE.

51.50 Top of impassable bluff, bears S.30°E., and N.30°W.

Set a flag "A" at top, and flag "B", bearing N.89°59'E.

near base below: from flag "B" I run on offset, N.0°1'W.

2.69 chs. to a point from which, flag "A" bears S.15°59'W.

Hence dist. offset from "A" to "B" = $2.69 \times \tan. 16^{\circ}0m.$,
= $2.69 \times .2867 = 0.77$ chs.

51.50 chs. + 2.69 chs. = 54.19 chs.

54.19 Offset S.89°59' W., 0.77 chs. to line.

Thence over rough rocks.

63.50 To avoid a rock 30 ft. high, I offset S.89°59'W., 0.40 chs.

65.00 Offset N.89°59'E., 0.40 chs. to line.