

East Boundary of T. 24 S., R. 2 W.,

CHAINS	<p>Soil, 3rd rate</p> <p>Densely covered with forest of pine, fir, hemlock, maple and laurel & dogwood</p> <p>Thick undergrowth of laurel, hazel, vine maple</p>
	<p>East Boundary of T. 24 S., R. 1 W. Carl S. Nicklin Contract No. 664 Dated May 23, 1896</p>
	<p>I begin at the cor. of Tps. 23 and 24 S., Rs. 1 E and 1 W., which is a post, 4 ft. 4 ins. sq. set 24 ins. in the ground, marked and witnessed, as described by the surveyor general</p> <p style="text-align: right;">Va. 19°30'E</p> <p>Thence I run South, bet. secs. 1 & 6 Ascend</p>
5.00	Top of spur, sloping NW, 100 ft. above cor. Begin descent
15.50	Foot of descend, 100 ft. below top of spur. Creek, 1 lk. wide, course W. Begin ascend.
22.75	Top of spur, sloping W., 150 ft. above creek Pass through slight ravine, then ascend
28.75	Top of Calipooia ridge, 400 ft. above creek, the divide bet. the head waters of the Willamette and Umpqua rivers, bears NE and SW
29.10	Trail from Oakland to Bohemia Begin descend. Trail bears E and W
	Diff. bet. measurements of 40.00 chs., by two sets of Chainmen, is 2 lks. position of middle point By 1st set, 40.02 chs. by 2nd set, 39.98 chs. the mean of which is
40.00	Set a basalt stone, 20x12x6 ins. 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which
	A fir, 12 ins. diam., bears N.44°E., 75 lks. dist. Marked $\frac{1}{4}$ S B T
	A fir, 30 ins. diam., bears N.86°W., 73 lks. dist. Marked $\frac{1}{4}$ S B T
	This cor. is on a steep hillside, sloping west