

## East Boundary of T. 24 S., R. 1 W

CHAINS	
57.50	Pass the W side of perpendicular bluff, 125 ft. above creek Descend
62.00	Creek, 1 lk. wide, 25 ft. below bluff, course NW Begin steep ascent
	Diff. bet. measurements of 80.00 chs. by two sets of chainmen, is 4 lks. position of middle point
	By 1st set, 80.02 chs.
	By 2nd set, 79.98 chs., the mean of which is
80.00	Set a hemlock post 4½ ft. long 4 ins. sq. 24 ins. in the ground, for cor. of secs. 25, 30, 31 & 36 marked T 24 S S 30 on NE., R 1 E S 31 on SE, S 36 on SW, and R 1 W S 25 on NW faces; with 5 notches on N and 1 notch on S edges, from which
	A hemlock, 6 ins. diam., bears N.56*E., 25 lks. dist.
	Marked T 24 S R 1 E S 30 B T
	A fir, 6 ins. diam., bears S.34*E., 22 lks. dist.
	Marked T 24 S R 1 E S 31 B T
	A cedar, 12 ins. diam., bears S.77*W., 36 lks. dist.
	Marked T 24 S R 1 W S 36 B T
	A cedar, 24 ins. diam., bears N.40*W., 65 lks. dist.
	Marked T 24 S R 1 W S 25 B T
	This cor. is on a steep hillside, sloping N
	Land, mountainous
	Soil, 3rd rate
	Timber, fir, hemlock, yew, alder, and maple
	Dense, undergrowth of vine-maple, rhododendron, mountain
	balm, hemlock, fir, cedar, and salal-berry.
	Land, mountainous and covered with dense undergrowth
	80.00 chs.
	South, bet. secs. 31 & 36
	Va. 19*30°E
10.50	Creek, 1 lk. wide, course N.10*E
18.25	Top of spur, sloping NW, 100 ft. above creek, noted at 62.00 chs., bet. secs. 25 & 30