

County Surveyor's Record, Douglas County, Oregon

-27761-

A

SOUTH BOUNDARY OF T. 24 S., R. 1 W., as
 Surveyed by Carl S. Nicklin, Deputy Surveyor
 Under Contract No. 664, Dated May 23, 1896.

CHAINS

Ts. 24 and 25 S., bet. Rs. 1 E., and 1 W.

The surrounding country being extremely rough and mountainous,
 there is no place suitable for such observation.

I began at the cor. of Ts. 24 and 25 S., Rs. 1 E. and 1 W.

July 18: At this cor., at 7 hrs. 5 m., A.M., l.m.t., I set off
 20°54'N. on decl. arc and 43°26' N., on lat. arc., and determine a
 true meridian with the solar.

Thence I run

West, on random line along the S. bdy. of T. 24 S., R. 1 W.,
 setting temp. $\frac{1}{4}$ sec. and sec. cors. at intervals of 40.00 chs.,
 for $5\frac{1}{2}$ miles; and at 549.50 chs., intersect E. bdy. of T. 25 S.,
 R. 2 W., 19.52 chs. S. of cor. of Ts. 24 and 25 S., R. 1 and
 2 W., which is a post, 2 ins. sq., 2 ft. above ground, marked
 and witnessed as described by the surveyor general.

I re-establish this cor. as follows:

Set a fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground,
 for cor. of T. 24 and 25 S., R. 2 W., on W. bdy. of T. 24 S.,
 R. 1 W., marked:

| | |
|--------------|-------------------------|
| T24S R2W S36 | on NW., and |
| T25S R2W S1 | on SW. faces; with |
| 6 notches | on N., W. and S. edges; |

from which,

A fir, 14 ins. diam., bears N. 16°W., 16 lks. dist.,
 marked: T 24 S R 2 W S 36 BT.

A fir, 14 ins. diam., bears S. 58°W., 33 lks. dist.,
 marked: T 25 S R 2 W S 1 BT.

This cor. is on a steep hillside sloping N., about 300 ft.

below the closing cor. of Ts. 24 and 25 S., R. 2 W.

At the point of intersection, 19.52 chs. S. of this cor.

Set a basalt stone, 16 x 10 x 10 ins., 12 ins. in the ground, for
 closing cor. of T. 24 and 25 S., R. 1 W., on E. bdy. of
 T. 25 S., R. 2 W., marked:

| | |
|-----------|--------------------------|
| 0 0 | on E. face, with |
| 6 grooves | on N., E., and S. faces; |

from which,

A fir, 12 ins. diam., bears N. 65°E., 67 lks. dist.,

marked: T 24 S R 1 W S 31 BT.