

County Surveyor's Record, Douglas County, Oregon

B

South Boundary of T. 24 S., R. 1 W.

CHAINS

A chincapin, 6 ins. diam., bears S, 12°E., 20 lks. dist.

marked: T 25 S R 1 W S 6 BT.

This cor. is on the top of a spur, sloping SW.

July 18, 1896.

From the closing cor., I run.

East, on a true line, along the S. bdy. of sec. 31.

Mag. decl. 28°30'E.

Descend.

9.65 Spur, sloping S., about 100 ft. below closing cor.

17.15 Mag. decl. 20°E.

27.90 Mag. decl. 17°30'E.

32.90 Mag. decl. 20°30'E.

40.90 Mag. decl. 11°E.

45.40 Spur, sloping SW., about 250 ft. below closing cor.

53.30 Creek, 1 lk. wide, course SW., about 75 ft. below top of last spur.

Ascend.

62.65 Top of spur, sloping S., about 100 ft. above creek.

79.40 Top of ridge, bears N. and S., about 50 ft. above spur last noted.

Begin descent.

99.67 Creek, 5 lks. wide, course S., about 200 ft. below ridge last noted.

Ascend.

109.40 Set a cedar post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked:

$\frac{1}{4}$  S on N. face;

from which,

Omission supplied on pp. 2776<sup>1</sup>/<sub>2</sub> -  $\frac{1}{4}$   
From photostat of original manuscript  
Book 413, pp. 291-294  
Copied August 3rd., 1937  
by Ira F. Rankin.