

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S R 1 W

CHAINS	
	Thence I run East on true line, along S boundary of Sec. 32 Mag. decl. 20°30'E Descend
31.50	Creek, 15 lks. wide, course S.15°W., about 200 ft. below sec. cor.
33.25	Creek, 6 lks. wide, course S.80°W., about 20 ft. below last creek Ascend
40.00	Set a hemlock post, 4 ft. long 4 ins. sq. 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face, from which A fir, 36 ins. diam., bears S.74°E., 28 lks. dist. Marked $\frac{1}{4}$ S B T A cedar, 14 ins. diam., bears N.43°W., 8 lks. dist. Marked $\frac{1}{4}$ S B T This corner is on a hillside, sloping N about 100 ft. above creek.
51.05	Top of spur, sloping N W about 50 ft. above $\frac{1}{4}$ sec. cor. Begin ascent
53.00	Creek, 6 lks. wide, course N.80°W., about 40 ft. below spur. Begin ascent.
80.00	Set a fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of 33, 4, 5, and 32 marked T 24 S S 33 on NE, R 1 W S 4 on SE, T 25 S S 5 on S W and S 32 on N W faces; with 2 notches on W and 4 notches on E edges; from which A fir, 8 ins. diam., bears N.60°E., 8 lks. dist. Marked T 24 S R 1 W S 33 B T A fir, 24 ins. diam., bears S.10°E., 51 lks. dist. Marked T 25 S R 1 W S 4 B T A fir, 12 ins. diam., bears S.51 $\frac{1}{2}$ °W., 6 lks. dist. Marked T 25 S R 1 W S 5 B T A fir, 12 ins. diam., bears N.44°W., 28 lks. dist. Marked T 24 S R 1 W S 32 B T This cor. is on a hillside, sloping N about 100 ft. above creek.