

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S., R. 1 W.

CHAINS	
	Thence I run East, on true line, along the S bdy. of sec. 35 Mag. decl. 15*E Descend
10.25	Enter creek bottom, 10 lks. wide, course S.80*E., about 160 ft. below sec. cor. Descend through creek.
12.48	Leave creek, course N.80*E
14.10	Same creek, SE about 185 ft. below sec. cor. Begin ascent
21.75	Top of spur, sloping SE about 75 ft. above last creek. Begin descent
25.00	Mag. decl. 18*E
35.25	McKinley Creek, 75 lks. wide, course S about 100 ft. below spur. Ascend
40.00	Set a basalt stone, 12x8x8 ins. 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which A fir, 60 ins. diam., bears N.50*E., 35 lks. dist. Marked $\frac{1}{4}$ S B T A fir, 20 ins. diam., bears S.5*E., 11 lks. dist. Marked $\frac{1}{4}$ S B T This cor. is on a hillside, sloping SW 50 ft. above McKin- ley Creek.
68.23	Top of spur, sloping NW about 150 ft. above $\frac{1}{4}$ sec. cor.
73.78	Top of spur, sloping NW about 200 ft. above $\frac{1}{4}$ sec. cor. Begin descent
80.00	Set a fir post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, for cor. of secs. 36, 1, 2, and 35; marked T 24 S S 36 on NE, R 1 W S 1 on SE, T 25 S S 2 on SW and S 35 on NW faces; with 5 notches on W and 1 notch on E edges; from which A fir, 16 ins. diam., bears N.14*E., 24 lks. dist. Marked T 24 S R 1 W S 36 B T A fir, 10 ins. diam., bears S.10*E., 20 lks. dist. Marked T 25 S R 1 W S 1 B T A pine, 48 ins. diam., bears S.15*W., 21 lks. dist.