

Subdivisions of T. 24 S., R. 1 W.

CHAINS	
	Ascend
30.27	A perpendicular bluff, facing S 20 ft. high, bears E., 10 lks. dist.
40.00	Set a basalt stone, 16x12x10 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which A fir, 30 ins. diam., bears S.41*E., 26 lks. dist. Marked $\frac{1}{4}$ S B T A chincapin, 6 ins. diam., bears N.19*W., 17 lks. dist. Marked $\frac{1}{4}$ S B T This cor. is on a steep hillside, sloping SW about 175 ft. above creek
44.05	Top of spur, sloping W., about 75 ft. above $\frac{1}{4}$ sec. cor. Descend
59.50	Spur, sloping W., about 100 ft. below last spur
66.03	Foot of descent. Creek, 20 lks. wide, course S.30*W Begin ascent Mag. decl. 19*E
72.49	Creek, 1 lk. wide, course E., about 50 ft. above creek; last noted
80.00	Set a basalt stone, 12x10x10 ins. 9 ins. in the ground, for cor. of secs. 11, 14, 15, and 10 marked with 4 notches on S and 2 notches on E edges, from which A fir, 16 ins. diam., bears N.36*E., 32 lks. dist. Marked T 24 S R 1 W S 11 B T A fir, 10 ins. diam., bears S.34*E., 27 lks. dist. Marked T 24 S R 1 W S 14 B T A fir, 24 ins. diam., bears S.2*W., 106 lks. dist. Marked T 24 S R 1 W S 15 B T A pine, 12 ins. diam., bears N.58 $\frac{1}{2}$ *W., 49 lks. dist. Marked T 24 S R 1 W S 10 B T This cor. is on a steep hillside, sloping E, about 50 ft. above creek, last noted