

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 1 W

CHAINS	
	From the cor. of secs. 34, 3, 4, and 33, which I set July 20, 1896
	I run North, 0°2'W., bet. secs. 33 and 34 descend
12.25	Perpendicular rock, 15 ft. high facing N
23.53	Creek, 2 lks. wide, course E about 250 ft. below sec. cor.
28.44	Creek, 10 lks. wide, course SE about 25 ft. below last creek
	From this point, a waterfall about 75 ft. high bears E 15 lks. dist.
	Ascend
40.00	Falls on a boulder, 10x8x3 ft. above ground. At exact point for $\frac{1}{4}$ sec. cor. I mark a cross and $\frac{1}{4}$ on W side from which A fir, 30 ins. diam., bears N.28°E., 32 lks. dist. Marked $\frac{1}{4}$ S. B T A chincapin, 6 ins. diam., bears S.63°W., 28 lks. dist. Marked $\frac{1}{4}$ S B T
	This cor. is about 175 ft. above creek Mag. decl. 21°E
46.05	Mag. decl. 15°E
58.00	Mag. decl. 17°E
80.00	Set a pine post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, for cor. of secs. 27, 34, 33 and 28, marked T 24 S S 27 on NE, R 1 W S 34 on SE., S 33 on SW., and S 28 on NW faces with 3 notches on E and 1 notch on S edges; from which A fir, 8 ins. diam., bears N.66°E., 34 lks. dist. Marked T 24 S R 1 W S 27 B T A chincapin, 6 ins. diam., bears S.34°E. 8 lks. dist. Marked T 24 S R 1 W S 34 B T A fir, 10 ins. diam., bears S.41°W., 27 lks. dist. Marked T 24 S R 1 W S 33 B T A chincapin, 8 ins. diam., bears N.47°W., 24 lks. dist. Marked T 24 S R 1 W S 28 B T
	This cor. is on top of a spur sloping S about 200 ft. above $\frac{1}{4}$ sec. cor.