

## Subdivisions of T. 24 S., R. 1 W

CHAINS	
	North, 0°3'W., on random line, bet. secs. 4 and 5
40.00	Set a temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect S bdy of T. 23 S., R. 1 W. 29 lks. E of cor. of secs. 33, 4, 5, and 32, which is a post, 4 ft. long, 4 ins. sq. set 24 ins. in the ground, marked and witnessed as described by the surveyor general
	Thence I run South, 15°E on true line, bet. secs. 4 and 5
	Descend
1.50	Dry creek-bed, course W., about 25 ft. below cor.
	Begin ascent
5.00	Top of spur, sloping W., about 50 ft. above dry creek-bed. Begin descent
9.06	Creek, 2 lks. wide, course N.80°W., about 25 ft. below spur, last noted
	Ascend
12.00	Creek, 1 lk. wide, course NW, about 25 ft. above last creek.
37.80	Top of ridge, bears N.70°E and S 70°W, the divide bet. the head waters of the Willamette and Umpqua rivers-- about 200 ft. above creek, last noted
	Descend.
38.40	Trail from Bohemia to Oakland, bears N.70°E., and S.70°W about 10 ft. below top of ridge.
39.94	Set a basalt stone, 16x12x12 ins. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face, from which A fir, 24 ins. diam., bears N.86 $\frac{1}{8}$ °E., 120 lks. dist. Marked $\frac{1}{4}$ S B T A fir, 36 ins. diam., bears N.15°W., 22 lks. dist. Marked $\frac{1}{4}$ S B T
	This cor. is on a steep hillside, sloping SE about 20 ft. below trail