

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 24 S., R. 1 W.

CHAINS		
	North 0°4'W., bet. secs. 19 and 20	
	Mag. decl. 20°E	
	Descend	
11.79	Creek, 7 lks. wide, course W., about 200 ft. below sec. cor.	
	Ascend	
16.03	Creek, 2 lks. wide, course S.20°W., about 100 ft. above last creek	
21.74	Enter same creek, course S.10°E., about 50 ft. above last crossing	
23.97	Leave creek, course S.10°W.	
40.00	Set a dog-wood post, 3½ ft. long, 4 ins. sq. 24 ins. in the ground, for ¼ sec. cor. marked ¼ S on W face, from which	
	A fir, 30 ins. diam., bears N.28½°E., 30 lks. dist.	
	Marked ¼ S B T	
	A fir, 30 ins. diam., bears S.56°W., 55 lks. dist.	
	Marked ¼ S B T	
	This cor. is on a hillside, sloping SW about 100 ft. above last point of crossing creek	
43.50	Enter land-slide, facing S	
45.25	Leave land-slide, facing S., about 50 ft. above ¼ sec. cor.	
72.20	Top of ridge, bears E and W about 300 ft. above land-slide	
	Descend	
80.00	Set a basalt stone, 20x16x8 ins. 16 ins. in the ground, for cor. of secs. 17, 20, 19, and 18 marked with 3 notches on S and 5 notches on E edges; from which	
	A fir, 16 ins. diam., bears N.70°E., 44 lks. dist.	
	Marked T 24 S R 1 W S 17 B T	
	A fir, 20 ins. diam., bears S.63°E., 24 lks. dist.	
	Marked T 24 S R 1 W S 20 B T	
	A fir, 12 ins. diam., bears S.45°W., 20 lks. dist.	
	Marked T 24 S R 1 W S 19 B T	