

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS

A fir, 12 ins. diam., bears S.63*W. 32 lks. dist.
marked T 25 S R 2 W S 1 B T.

A fir, 14 ins. diam., bears N.25*W. 15 lks. dist.
marked T 24 S R 2 W S 36 B T.

From this cor. I run North on the east boundary of Sec.
36.

Var. 20*E.

And at 40.03 chs. find the $\frac{1}{4}$ sec. cor. and at 80.05 chs.
find the cor. to secs 25, 36, 30 and 31. The bearing
of the range line is therefore north agreeing with the
notes supplied by the Surveyor General.

I now return to the SE. cor. of the Tp.

Thence I run N.89*48'W. along the South boundary of sec.
36.

Var. 20*E.

At 39.97 find the $\frac{1}{4}$ sec. cor. and at 79.95 find the cor.
to secs. 35 and 36. The course of the South boundary
is therefore as above stated.

With the above named true bearings, the subdivision lines
of the eastern tier of sections will be run as re-
quired by the printed instructions, and my chaining
practically agrees with the original survey.

I commence at the cor. to secs. 1, 2, 35 & 36 on the
South boundary of the Tp., which is a post, 4 ft. long,
and 4 ins. sq. firmly set in the ground, marked T 22
S S 36 on the NE., R 2 W S 1 on the SE., T 25 S S 2 on
the SW. and S 35 on the NW. faces, with 5 notches on
the W. and 1 notch on the E. edges, from which

A fir, 30 ins. diam., bears N.21*E. 18 lks. dist.
marked T 24 S R 2 W S 36 B T.

A fir, 41 ins. diam., bears S.20*E. 69 lks. dist.
marked T 25 S R 2 W S 1 B T.

A maple, 8 ins. diam., bears S.32*W. 15 lks. dist.
marked T 25 S R 2 W S 2 B T.