

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS

SW. and S 13 on NW. faces with 3 notches on N. and S. edges, from which

A fir, 24 ins. diam., bears N.10*E. 20 lks. dist. marked T 24^SR 1 W S 18 B T.

A fir, 12 ins. diam., bears S.43*E. 21 lks. dist. marked T 24 S R 1 W S 19 B T.

A fir, 18 ins. diam., bears S.46*W. 41 lks. dist. marked T 24 S R 2 W S 24 B T.

A fir, 12 ins. diam., bears N.30*W. 10 lks. dist. marked T 24 S R 2 W S 13 B T.

Thence I run

West on a true line bet. secs. 13 and 24.

Var. 20*E.

Through heavy timber, ascend about 500 ft.

39.75 Set a basalt stone 18x12x12 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which

A hemlock, 18 ins. diam., bears S.63*W. 25 lks. dist. marked $\frac{1}{4}$ S B T.

A fir, 30 ins. diam., bears N.55*30'W. 33 lks. dist. marked $\frac{1}{4}$ S B T.

57.00 Top of ridge, course N. & S. and descend about 300 ft. to

79.50 The cor. to secs. 13, 14, 23 and 24.

Land, mountainous and heavily timbered with fir and hemlock, with dense undergrowth of chinquapin and rhododendron, 79.50 chs.

Soil, rocky, 4th rate.

Sept. 8, 1894.

N.0*1'W. bet. secs. 13 & 14.

Var. 20*E.

Through heavy timber, ascend about 75 ft. to

3.50 Top of spur, course SW. and descend about 60 ft. to

7.75 Creek, 1 lk. wide, course SW. and ascend about 400 ft.

40.00 Set a post 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face, from which